![ProComSol logo] **PROCOMSOL**
Process Communications Solutions

HART COMMUNICATION PROTOCOL

TAB-DROID-C1D2-MOBI
Android Class 1 Div 2 Tablet HART Communicator Kit, mobiLink

Description:

Combines all components needed for an Intrinsically Safe cost-effective HART Hand-Held Communicator for Class 1, Division 2 applications.

Includes:

- TAB-EX 03 rugged tablet with Bluetooth, Android 13, WI-FI, 4GB RAM, 64GB Storage Memory, 8 inch Touch Screen.
- DevComDroid HART Communicator App
- MOBI-HART Intrinsically Safe HART Modem
- Complete HART DD Library
- One year Update Subscription (SUB-1YR)
- Loop Resistor, 250 Ohm
- Rugged hard plastic case with carrying handle

All components installed, setup, and ready to go!

Providing Advanced Process Communication Products since 2005

Specifications:

TAB-EX 03

Operating System	Android 13
Screen	8" TFT (1920 x 1200 pixels) Multi-Touch Screen
Communications	Bluetooth 5.0, WLAN 802.11 a/b/g/n/ac/ax
Bluetooth Modem Range	30 ft (10m)
Memory	4 GB RAM, 64 GB Storage
Camera	13 Megapixel rear, 5 Megapixel front
Battery	5050 mAh
Safety IECEx:	Ex ic IIC T5 Gc IP64, Ex ic IIIC T85°C Dc
Safety ATEX:	II 3G Ex ic IIC T5 Gc IP64, II 3D Ex ic IIIC T85°C Dc
Safety CSA	Class I, Division 2, Groups A-D; T5

DevComDroid HART Communicator App for Android

DD Library	Included
Generic DD	Included
DD Updates	Quarterly updates for 1 year free

MOBI-HART Intrinsically Safe HART Modem

Dimensions	6.9" x 2.9" x 1.3" (175 mm x 74 mm x 32 mm)
Total Unit Weight	11.6 oz (330 g) including Batteries
Protection Class	IP 54
Intrinsic safety	EX ia IIB, Ui = 30 V, Ci 5 nF, Li negligible low FISCO field device
Isolation	1500 VDC between USB and field device connections
HART Specifications	HART 4, HART 5, HART 6, HART 7, *wireless*HART HART Physical Layer Spec HCF_SPEC-54
Power	3x AA Batteries
Current Draw	100mA

Loop Resistor, 250 Ohm

Power Rating	1 Watt

Carrying Case

Size	17" L x 12" W x 3-1/2" H

Note: For full specifications see individual data sheets.

ProComSol, Ltd

Process Communications Solutions

Phone: 216.221.1550
Toll Free: 877.221.1551
Email: sales@procomsol.com
Web: www.procomsol.com