





HM-USB-PWR USB HART Modem, Integrated Power Supply





Description:

Perform HART communications between a HART transmitter and a Windows or Android device using USB. Unit can also supply power to the HART transmitter for easy setup.

Features and Benefits:

- Combination HART Modem and Power Supply for HART transmitters
- +24Vdc supply from USB connection or AC to USB adapter
- 1500 Vdc Opto Isolation between HART and USB circuits
- Supports all USB versions
- Integral standard USB type A connector
- Heavy duty HART Mini-grabber connectors
- Designed to meet HART Physical Layer Spec HCF SPEC-54
- Self powered, no external power supply or batteries needed
- Built-in Loop Resistor
- Easy to install Virtual Serial Port for any Windows application
- Rugged ABS plastic enclosure
- Works with DevCom2000 and DevComDroid and many other HART Windows software
- 1 Year warranty







Specifications:

Enclosure

Material High strength ABS Plastic

Dimensions 5.5" x 2.5" x 1.0" (140mm x 64mm x 25mm)

Total Unit Weight 8 oz (227 g)

<u>Cables</u>

Cable Length 6' (1.8 m)
USB Cable Connector USB Type A

HART

Interface Capacitive and transformer coupling

Output 600 mVpp Leakage < 10 uA Isolation Voltage 1500 Vdc

Specifications HART 4, HART 5, HART 6, HART 7, wirelessHART

HART Physical Layer Spec HCF SPEC-54

Computer

Operating System Windows 7 or higher

Android 4.3 or higher

USB

Specifications USB 1.1, USB 2.0

Power USB port provides power to unit Current Draw 30mA (Modem Only Mode) 225mA (Power Supply Mode)

Environmental

Operating Temperature 0 degC to 50 degC (32 degF to 122 degF)
Storage Temperature -40 degC to 85 degC (-40 degF to 185 degF)

Humidity 0% to 95% (non-condensing)

Compliances

MK-1054, 06/13/2023

CE Certification EN 61326 (EMC), Directive 2011/65/EU (RoHS)

ProComSol, Ltd

Process Communications Solutions

Phone: 216.221.1550
Toll Free: 877.221.1551
Email: sales@procomsol.com
Web: www.procomsol.com